

SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 1/17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: C2H2F4 46,7577 %;C3H2F4 53,2423 %

Trade name: R 513A

Other Name: HFC-1234yf 56 % (w/w); R-134a 44 % (w/w)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.

Refrigerant.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas AS Telephone: +4723177200

Postboks 13 Nydalen

N-0409 Oslo

E-mail: sds.ren@linde.com

1.4 Emergency telephone number: +47 22 59 13 00 (24h - Giftinformasjonssentralen)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure Liquefied gas H280: Contains gas under pressure; may explode if

heated.

2.2 Label Elements



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 2/17



Signal Word: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.

Precautionary Statements

General None.

Prevention: None.

Response: None.

Storage: P403: Store in a well-ventilated place.

Disposal None.

Supplemental information

EIGA-0783: Contains fluorinated greenhouse gases

EIGA-As: Asphyxiant in high concentrations.

2.3 Other hazards Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Norflurane	C2H2F4	46,7577%	811-97-2	01- 2119459374- 33	-	
2,3,3,3- Tetrafluoropropene	C3H2F4	53,2423%	754-12-1	01- 0000019665- 61	-	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 3/17

Classification

Chemical name	Classification		Notes
Norflurane	CLP:	Press. Gas Liquef. Gas;H280	
2,3,3,3-Tetrafluoropropene	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	

CLP: Regulation No. 1272/2008.

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy

to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available,

flush an additional 15 minutes.

Skin Contact: Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and

effects, both acute and

delayed:

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to

rapid evaporative cooling. Irregular cardiac activity. Dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to

rapid evaporative cooling.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate

medical advice/attention.



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 4/17

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Material will not burn. In case of fire in the surroundings: use appropriate

extinguishing agent.

Unsuitable extinguishing

media:

None.

5.2 Special hazards arising from the

substance or mixture:

Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: If involved in a fire the following toxic and/or corrosive fumes may be produced

by thermal decomposition: Carbon oxides Hydrogen fluoride

; Carbonyl difluoride

5.3 Advice for firefighters

Special fire fighting

procedures:

In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate

the source of the fire or let it burn out.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so.



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 5/17

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation.

6.4 Reference to other sections: Refer to sections 8 and 13.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water. acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet

transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

caps or plugs and container caps where supplied as soon as container is

disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty

operating container valve discontinue use and contact supplier. Never attempt to

7.3 Specific end use(s):

None.



SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 6/17

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

DNEL-Values

Critical component	Туре	Value	Remarks
Norflurane	Workers - Inhalation,	13936	Repeated dose toxicity
	Systemic, long-term	mg/m3	
2,3,3,3-Tetrafluoropropene	Workers - Inhalation,	950 mg/m3	Repeated dose toxicity
	Systemic, long-term		
	Workers - Eyes, Local effect		Low hazard (no threshold derived)

PNEC-Values

Critical component	Туре	Value	Remarks
Norflurane	Aquatic (marine water)	0,01 mg/l	-
Norflurane	Sewage treatment plant	73 mg/l	-
Norflurane	Sediment (freshwater)	0,75 mg/kg	-
Norflurane	Aquatic (freshwater)	0,1 mg/l	-
2,3,3,3-Tetrafluoropropene	Aquatic (freshwater)	0,1 mg/l	-
2,3,3,3-Tetrafluoropropene	Aquatic (marine water)	0,01 mg/l	-
2,3,3,3-Tetrafluoropropene	Sediment (freshwater)	1,51 mg/kg	-
2,3,3,3-Tetrafluoropropene	Soil	1,49 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 7/17

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to

assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task

being performed and the risks involved.

Eye/face protection: Safety eyewear, goggles or face-shield to EN166 should be used to avoid

exposure to liquid splashes. Wear eye protection to EN 166 when using gases.

Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection: Guideline: EN 388 Protective gloves against mechanical risks.

Additional Information: Wear working gloves while handling containers

Body protection: No special precautions.

Other: Wear safety shoes while handling containers

Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection: Not required.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Specific risk management measures are not required beyond good industrial

hygiene and safety procedures. Do not eat, drink or smoke when using the

product.

Environmental exposure

controls:

For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Gas

Form: Liquefied gas
Color: C2H2F4: Colorless

C3H2F4: Colorless

Odor: C2H2F4: faint ethereal

C3H2F4: Ethereal odor



Odor threshold is subjective and is inadequate to warn of over

SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

 Issue Date:
 05.07.2018
 Version: 1.0
 SDS No.: 000010047430

 Last revised date:
 07.04.2021
 8/17

exposure.

pH: Not applicable.Melting Point: No data available.

Boiling Point: -29,2 °C
Sublimation Point: Not applicable.

Critical Temp. (°C): 96,5 °C

Flash Point:Not applicable to gases and gas mixtures. **Evaporation Rate:**Not applicable to gases and gas mixtures.

Flammability (solid, gas):

Flammability Limit - Upper (%):

Flammability Limit - Lower (%):

Not applicable.

Not applicable.

Vapor pressure:No reliable data available.Vapor density (air=1):3,82 (calculated) (15 °C)

Relative density: No data available.

Solubility(ies)

Odor Threshold:

Solubility in Water: No data available.

Partition coefficient (n-octanol/water):Not known.Autoignition Temperature:Not applicable.Decomposition Temperature:Not known.

Viscosity

Kinematic viscosity:No data available.Dynamic viscosity:No data available.Explosive properties:Not applicable.Oxidizing properties:Not applicable.

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined

spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1 Reactivity: No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of hazardous

reactions:

None.



SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 9/17

10.4 Conditions to avoid: Open flames and high energy ignition sources. The product is not flammable in air

under ambient conditions of temperature and pressure. When pressurised with air or oxygen, the mixture may become flammable. Certain mixtures of HCFCs or HFCs with chloring may become flammable as reactive under sectain and disease.

with chlorine may become flammable or reactive under certain conditions.

10.5 Incompatible Materials: No reaction with any common materials in dry or wet conditions. Strong alkalis.

Strong oxides. Alkali earth metals. Chemically-active metals (such as calcium,

powdered aluminum, zinc, and magnesium)

10.6 Hazardous Decomposition

Products:

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral

Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal

Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation

Product Based on available data, the classification criteria are not met.

Component Information

Tetrafluoropropene

2,3,3,3-

LC 50 (Rat): > 405000 ppm

Repeated dose toxicity
Component Information

Norflurane NOAEL (Rat(Female, Male), Inhalation, 2 yr): 50.000 ppm(m) Inhalation

Experimental result, Key study

Skin Corrosion/Irritation

Product Based on available data, the classification criteria are not met.



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 10/17

Serious Eye Damage/Eye Irritation

Product Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization

Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product Based on available data, the classification criteria are not met.

In vitro

Component Information

2,3,3,3-Tetrafluoropropene Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)):

Mutagenic

In vivo

Component Information

2,3,3,3-Tetrafluoropropene Chromosome aberration (OECD Guideline 474 (Mammalian Erythrocyte

Micronucleus Test)): Negative.

Carcinogenicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity (Fertility)
Component Information

2,3,3,3-Tetrafluoropropene Rat NOAEL - No Observable Adverse Effect Level: 50.000 ppm

Developmental toxicity (Teratogenicity)

Component Information

2,3,3,3-Tetrafluoropropene Rat Inhalation (OECD Guideline 414 (Prenatal Developmental Toxicity Study))

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.



SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430 Last revised date: 07.04.2021 11/17

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

Other Relevant Toxicity Information

2,3,3,3-Tetrafluoropropene Cardiac sensitisation threshold limit

>120000 ppm Beagle (dog)LOAEC

Cardiac sensitisation threshold limit

120000 ppm Beagle (dog)NOAEC

Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances

these effects.

Norflurane Cardiac sensitisation threshold limit

40000 ppm

Beagle (dog)NOAEC

Cardiac sensitisation threshold limit

80000 ppm

Beagle (dog)LOAEC

Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances

these effects. May produce irregular heart beat and nervous symptoms.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product No ecological damage caused by this product.

Acute toxicity - Fish Component Information

Norflurane LC 50 (Oncorhynchus mykiss, 96 h): 450 mg/l (semi-static) Remarks: Experimental

result, Key study

2,3,3,3-Tetrafluoropropene LC 50 (Carp (Cyprinus carpio), 96 h): > 197 mg/l

SDS_NO - 000010047430



SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 12/17

Acute toxicity - Aquatic Invertebrates

Component Information

Norflurane EC 50 (Daphnia magna, 24 h): 960 mg/l (Static) Remarks: Experimental result, Key

study

2,3,3,3-Tetrafluoropropene EC 50 (Water flea (Daphnia magna), 48 h): > 100 mg/l

Toxicity to Aquatic Plants
Component Information

2,3,3,3-Tetrafluoropropene NOEC (Algae (Pseudokirchneriella subcapitata), 72 h): > 75 mg/l (OECD Guideline

201 (Freshwater Alga and Cyanobacteria, Growth Inhibition Test))

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

Biodegradation

Component Information

Norflurane 3 % (28 d) Detected in water. Experimental result, Key study

2,3,3,3-Tetrafluoropropene < 5 % (28 d, OECD 301F/ISO 9408/EEC 92/69/V, C.4-D)

12.3 Bioaccumulative potential

Product The subject product is expected to biodegrade and is not expected to persist for

long periods in an aquatic environment.

12.4 Mobility in soil

Product Because of its high volatility, the product is unlikely to cause ground or water

pollution.

Component Information

Norflurane Henry's Law Constant: 8.580 MPa (25 °C)

12.5 Results of PBT and vPvB

assessment

Product Not classified as PBT or vPvB.



SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 13/17

12.6 Other adverse effects:

Global Warming Potential

Global warming potential: 631,4

Contains fluorinated greenhouse gases When discharged in large quantities may contribute to the greenhouse effect. For GWP value of mixture and

quantities, refer to container label.

Component Information

Norflurane <u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation</u>

517/2014/EU on FGGs

- Global warming potential: 1430 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures

2,3,3,3-Tetrafluoropropene

EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation

517/2014/EU on FGGs

- Global warming potential: 4 Annex 2: Other fluorinated greenhouse gases subject

to reporting in accordance with Article 19; Section 1: Unsaturated

hydro(chloro)fluorocarbons

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Avoid discharges to atmosphere. Do not discharge into any place where its

accumulation could be dangerous. Refer to manufacturer or supplier for

information on recovery or recycling.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to

national, state, or local laws.

European Waste Codes

Container: 14 06 01*: chlorofluorocarbons, HCFC, HFC



SAFETY DATA SHEET C2H2F4 46,7577 %;C3H2F4 53,2423 %

05.07.2018 Issue Date: Version: 1.0 SDS No.: 000010047430 Last revised date: 07.04.2021 14/17

SECTION 14: Transport information

ADR

14.1 UN Number: UN 1078

14.2 UN Proper Shipping Name: REFRIGERANT GAS, N.O.S.(2,3,3,3-Tetrafluoropropene, 1,1,1,2-

Tetrafluoroethane)

14.3 Transport Hazard Class(es)

Class: 2 Label(s): 2.2 Hazard No. (ADR): 20 Tunnel restriction code: (C/E)

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

RID

14.1 UN Number: UN 1078

14.2 UN Proper Shipping Name REFRIGERANT GAS, N.O.S.(2,3,3,3-Tetrafluoropropene, 1,1,1,2-

Tetrafluoroethane)

14.3 Transport Hazard Class(es)

Class: 2 Label(s): 2.2

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

IMDG

14.1 UN Number: UN 1078

REFRIGERANT GAS, N.O.S.(2,3,3,3-Tetrafluoropropene, 1,1,1,2-14.2 UN Proper Shipping Name:

Tetrafluoroethane)

14.3 Transport Hazard Class(es)

2.2 Class: Label(s): 2.2 EmS No.: F-C, S-V

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 15/17

IATA

14.1 UN Number: UN 1078

14.2 Proper Shipping Name: Refrigerant gas, n.o.s. (2,3,3,3-Tetrafluoropropene, 1,1,1,2-

Tetrafluoroethane)

14.3 Transport Hazard Class(es):

Class: 2.2 Label(s): 2.2

14.4 Packing Group: –
14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

Other information

Passenger and cargo aircraft: Allowed. Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from

the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure

adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:Not applicable

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SDS NO - 000010047430



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 16/17

SECTION 16: Other information

Revision Information: Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include

but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(http://www.atsdr.cdc.gov/).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search

European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling

quide", as amended.

International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and

oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database

Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network

TOXNET (http://toxnet.nlm.nih.gov/index.html)

Threshold Limit Values (TLV) from the American Conference of Governmental

Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 as amended.	Classification procedure
Gases under pressure, Liquefied gas	On basis of test data

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.



Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047430

Last revised date: 07.04.2021 17/17

Training information: Users of breathing apparatus must be trained. The hazard of asphyxiation is often

overlooked and must be stressed during operator training. Ensure operators

understand the hazards.

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Liq. Gas, H280

Other information: Before using this product in any new process or experiment, a thorough material

compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting

from its use can be accepted.

Last revised date: 07.04.2021

Disclaimer: This information is provided without warranty. The information is believed to be

correct. This information should be used to make an independent determination of

the methods to safeguard workers and the environment.