



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016
Last revised date: 13.05.2020

Version: 1.0

SDS No.: 000010035817
1/20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Trade name: R448A

Other Name: HFC-32 26 % (w/w); HFC-125 26 % (w/w); HFC-134a 21 % (w/w); HFC-1234yf 20 % (w/w); HFC-1234ze 7 % (w/w)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Refrigerant.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas AS
Postboks 13 Nydalen
N-0409 Oslo Norway

Telephone: +4723177200

E-mail: sds.ren@linde.com

1.4 Emergency telephone number: +47 22 59 13 00 (24h - Giftinformasjonssentralen)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure

Liquefied gas

H280: Contains gas under pressure; may explode if heated.

2.2 Label Elements



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 2/20



Signal Word: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.

Precautionary Statements

General None.

Prevention: None.

Response: None.

Storage: P403: Store in a well-ventilated place.

Disposal None.

Supplemental information

EIGA-0783: Contains fluorinated greenhouse gases
 EIGA-As: Asphyxiant in high concentrations.

2.3 Other hazards Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
1,3,3,3-tetrafluoroprop-1-ene	C3H2F4	5,2962%	29118-24-9	01-0000019758-54	-	
2,3,3,3-Tetrafluoropropene	C3H2F4	15,1320%	754-12-1	01-0000019665-61	-	
Norflurane	C2H2F4	17,7587%	811-97-2	01-2119459374-33	-	
Pentafluoroethane	C2HF5	18,6912%	354-33-6	01-2119485636-25	-	



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 3/20

Difluoromethane	CH2F2	43,1219%	75-10-5	01-2119471312-47	-	
-----------------	-------	----------	---------	------------------	---	--

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements.

All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Classification		Notes
1,3,3,3-tetrafluoroprop-1-ene	CLP:	Press. Gas Liq. Gas;H280	
2,3,3,3-Tetrafluoropropene	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
Norflurane	CLP:	Press. Gas Liquef. Gas;H280	
Pentafluoroethane	CLP:	Press. Gas Liquef. Gas;H280	
Difluoromethane	CLP:	Press. Gas Liquef. Gas;H280, Flam. Gas 1;H220	

CLP: Regulation No. 1272/2008.

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date:	09.11.2016	Version: 1.0	SDS No.: 000010035817
Last revised date:	13.05.2020		4/20

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.

Unsuitable extinguishing media: None.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Carbon oxides Carbonyl halides Hydrogen fluoride ; Hydrogen chloride

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date:	09.11.2016	Version: 1.0	SDS No.: 000010035817
Last revised date:	13.05.2020		5/20

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
- 6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so.
- 6.3 Methods and material for containment and cleaning up: Provide adequate ventilation.
- 6.4 Reference to other sections: Refer to sections 8 and 13.

SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling: Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 6/20

7.2 Conditions for safe storage, including any incompatibilities: Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

DNEL-Values

Critical component	Type	Value	Remarks
1,3,3,3-tetrafluoroprop-1-ene	Worker - inhalative, long-term - systemic	3902 mg/m3	-
2,3,3,3-Tetrafluoropropene	Workers - Inhalation, Systemic, long-term	950 mg/m3	Repeated dose toxicity
	Workers - Eyes, Local effect		
Norflurane	Workers - Inhalation, Systemic, long-term	13936 mg/m3	Repeated dose toxicity
Pentafluoroethane	Workers - Inhalation, Systemic, long-term	16444 mg/m3	Repeated dose toxicity
Difluoromethane	Workers - Inhalation, Systemic, long-term	7035 mg/m3	Repeated dose toxicity

PNEC-Values

Critical component	Type	Value	Remarks
--------------------	------	-------	---------



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016
Last revised date: 13.05.2020

Version: 1.0

SDS No.: 000010035817
7/20

1,3,3,3-tetrafluoroprop-1-ene	Aquatic (freshwater)	0,1 mg/l	-
1,3,3,3-tetrafluoroprop-1-ene	Aquatic (intermit. releases)	1 mg/l	-
2,3,3,3-Tetrafluoropropene	Aquatic (freshwater)	0,25 mg/l	-
2,3,3,3-Tetrafluoropropene	Aquatic (marine water)	0,025 mg/l	-
2,3,3,3-Tetrafluoropropene	Soil	0,72 mg/kg	-
2,3,3,3-Tetrafluoropropene	Sediment (marine water)	0,135 mg/kg	-
2,3,3,3-Tetrafluoropropene	Sediment (freshwater)	1,35 mg/kg	-
Norflurane	Aquatic (marine water)	0,01 mg/l	-
Norflurane	Sewage treatment plant	73 mg/l	-
Norflurane	Sediment (freshwater)	0,75 mg/kg	-
Norflurane	Aquatic (freshwater)	0,1 mg/l	-
Pentafluoroethane	Aquatic (freshwater)	0,1 mg/l	-
Pentafluoroethane	Sediment (freshwater)	0,6 mg/kg	-
Difluoromethane	Aquatic (freshwater)	0,142 mg/l	-
Difluoromethane	Sediment (freshwater)	0,534 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 8/20

Individual protection measures, such as personal protective equipment

- General information:** A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved.
- Eye/face protection:** Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
- Skin protection**
- Hand Protection:** Guideline: EN 388 Protective gloves against mechanical risks. Additional Information: Wear working gloves while handling containers
- Body protection:** No special precautions.
- Other:** Wear safety shoes while handling containers. Guideline: ISO 20345 Personal protective equipment - Safety footwear.
- Respiratory Protection:** Not required.
- Thermal hazards:** No precautionary measures are necessary.
- Hygiene measures:** Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
- Environmental exposure controls:** For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state:** Gas
- Form:** Liquefied gas
- Color:** C3H2F4: Colorless
C3H2F4: Colorless
C2H2F4: Colorless
C2HF5: Colorless
CH2F2: Colorless
- Odor:** C3H2F4: Slight ether-like odor



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 9/20

<p>Odor Threshold:</p> <p>pH:</p> <p>Melting Point:</p> <p>Boiling Point:</p> <p>Sublimation Point:</p> <p>Critical Temp. (°C):</p> <p>Flash Point:</p> <p>Evaporation Rate:</p> <p>Flammability (solid, gas):</p> <p>Flammability Limit - Upper (%):</p> <p>Flammability Limit - Lower (%):</p> <p>Vapor pressure:</p> <p>Vapor density (air=1):</p> <p>Relative density:</p> <p>Solubility(ies)</p> <p style="padding-left: 20px;">Solubility in Water:</p> <p>Partition coefficient (n-octanol/water):</p> <p>Autoignition Temperature:</p> <p>Decomposition Temperature:</p> <p>Viscosity</p> <p style="padding-left: 20px;">Kinematic viscosity:</p> <p style="padding-left: 20px;">Dynamic viscosity:</p> <p>Explosive properties:</p> <p>Oxidizing properties:</p>	<p>C3H2F4: Ethereal odor C2H2F4: faint ethereal C2HF5: faint ethereal CH2F2: Odorless</p> <p>Odor threshold is subjective and is inadequate to warn of over exposure.</p> <p>Not applicable.</p> <p>No data available.</p> <p>>= -45,9 °C</p> <p>Not applicable.</p> <p>No data available.</p> <p>Not applicable to gases and gas mixtures.</p> <p>Not applicable to gases and gas mixtures.</p> <p>Non-Flammable Gas</p> <p>Not applicable.</p> <p>Not applicable.</p> <p>1.120 kPa (21,1 °C)</p> <p>3,04 (calculated) (15 °C)</p> <p>No data available.</p> <p>No data available.</p> <p>Not known.</p> <p>Not applicable.</p> <p>Not known.</p> <p>No data available.</p> <p>No data available.</p> <p>Not applicable.</p> <p>Not applicable.</p>
---	--

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Minimum ignition temperature: 628 °C

SECTION 10: Stability and reactivity

10.1 Reactivity: No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability: Stable under normal conditions.



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 10/20

10.3 Possibility of hazardous reactions:	None.
10.4 Conditions to avoid:	Open flames and high energy ignition sources. The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air or oxygen, the mixture may become flammable. Certain mixtures of HCFCs or HFCs with chlorine may become flammable or reactive under certain conditions.
10.5 Incompatible Materials:	No reaction with any common materials in dry or wet conditions. Alkali metals. Alkali earth metals. Chemically-active metals (such as calcium, powdered aluminum, zinc, and magnesium)
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation Product Based on available data, the classification criteria are not met.

Component Information

1,3,3,3-tetrafluoroprop-1-ene LC 50 (Rat, 4 h): > 965 mg/l

2,3,3,3-Tetrafluoropropene LC 50 (Rat): > 405000 ppm

Repeated dose toxicity

Component Information

Norflurane NOAEL (Rat(Female, Male), Inhalation, 2 yr): 50.000 ppm(m) Inhalation
 Experimental result, Key study



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 11/20

Pentafluoroethane NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): >= 50.000 ppm(m) Inhalation
 Experimental result, Key study

Difluoromethane NOAEL (Rat(Female, Male), Inhalation, 28 d): 49.500 ppm(m) Inhalation
 Experimental result, Supporting study

**Skin Corrosion/Irritation
 Product**

Based on available data, the classification criteria are not met.

Component Information

1,3,3,3-tetrafluoroprop-1-ene (Rabbit): Not classified as an irritant.

**Serious Eye Damage/Eye Irritation
 Product**

Based on available data, the classification criteria are not met.

**Respiratory or Skin Sensitization
 Product**

Based on available data, the classification criteria are not met.

Component Information

**Germ Cell Mutagenicity
 Product**

Based on available data, the classification criteria are not met.

In vitro

Component Information

2,3,3,3-Tetrafluoropropene Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)): Mutagenic

In vivo

Component Information

2,3,3,3-Tetrafluoropropene Chromosome aberration (OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)): Negative.

**Carcinogenicity
 Product**

Based on available data, the classification criteria are not met.

**Reproductive toxicity
 Product**

Based on available data, the classification criteria are not met.

**Reproductive toxicity (Fertility)
 Component Information**

2,3,3,3-Tetrafluoropropene Rat NOAEL - No Observable Adverse Effect Level: 50.000 ppm



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 12/20

Developmental toxicity (Teratogenicity)

Component Information

2,3,3,3-Tetrafluoropropene Rat Inhalation (OECD Guideline 414 (Prenatal Developmental Toxicity Study))

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

Other Relevant Toxicity Information

Difluoromethane

Cardiac sensitisation threshold limit
 >350000 ppm
 Beagle (dog)LOAEC

Cardiac sensitisation threshold limit
 350000 ppm
 Beagle (dog)NOAEC

Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects.

Pentafluoroethane

Cardiac sensitisation threshold limit
 100000 ppm
 Beagle (dog)NOAEC

Cardiac sensitisation threshold limit
 75000 ppm
 Beagle (dog)LOAEC

Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects. May produce irregular heart beat and nervous symptoms.



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 13/20

Norflurane	Cardiac sensitisation threshold limit 40000 ppm Beagle (dog)NOAEC Cardiac sensitisation threshold limit 80000 ppm Beagle (dog)LOAEC Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects. May produce irregular heart beat and nervous symptoms.
2,3,3,3-Tetrafluoropropene	Cardiac sensitisation threshold limit >120000 ppm Beagle (dog)LOAEC Cardiac sensitisation threshold limit 120000 ppm Beagle (dog)NOAEC Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product No ecological damage caused by this product.

Acute toxicity - Fish

Component Information

1,3,3,3-tetrafluoroprop-1-ene NOEC (Carp (Cyprinus carpio), 96 h): > 117 mg/l

2,3,3,3-Tetrafluoropropene LC 50 (Carp (Cyprinus carpio), 96 h): > 197 mg/l

Norflurane LC 50 (Oncorhynchus mykiss, 96 h): 450 mg/l (semi-static) Remarks: Experimental result, Key study

Pentafluoroethane LC 50 (Oncorhynchus mykiss, 96 h): 450 mg/l (semi-static) Remarks: Read-across



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 14/20

from supporting substance (structural analogue or surrogate), Weight of Evidence study

Difluoromethane LC 50 (Various, 96 h): 1.507 mg/l Remarks: QSAR QSAR, Key study

Acute toxicity - Aquatic Invertebrates

Component Information

- 1,3,3,3-tetrafluoroprop-1-ene LC 50 (Water flea (Daphnia magna), 48 h): > 160 mg/l
- 2,3,3,3-Tetrafluoropropene EC 50 (Water flea (Daphnia magna), 48 h): > 100 mg/l
- Norflurane EC 50 (Daphnia magna, 24 h): 960 mg/l (Static) Remarks: Experimental result, Key study
- Pentafluoroethane EC 50 (Daphnia magna, 48 h): > 200 mg/l (Static) Remarks: Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study
- Difluoromethane EC 50 (Daphnid, 48 h): 652 mg/l Remarks: QSAR QSAR, Key study

Chronic Toxicity - Aquatic Invertebrates

Component Information

- Pentafluoroethane EC 50 (16 d): 12 mg/l

Toxicity to Aquatic Plants

Component Information

- 1,3,3,3-tetrafluoroprop-1-ene NOEC (Green algae (Selenastrum capricornutum), 72 h): > 170 mg/l
- 2,3,3,3-Tetrafluoropropene NOEC (Algae (Pseudokirchneriella subcapitata), 72 h): > 75 mg/l (OECD Guideline 201 (Freshwater Alga and Cyanobacteria, Growth Inhibition Test))
- Pentafluoroethane EC 50 (Green Algae, 72 h): 142 mg/l
- Difluoromethane EC 50 (Alga, 96 h): 142 mg/l

12.2 Persistence and Degradability Product

Not applicable to gases and gas mixtures..



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 15/20

Component Information

1,3,3,3-tetrafluoroprop-1-ene Not readily biodegradable. Inorganic compound.

Biodegradation

Component Information

2,3,3,3-Tetrafluoropropene < 5 % (28 d, OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D)

Norflurane 3 % (28 d) Detected in water. Experimental result, Key study

Pentafluoroethane 5 % (28 d) Detected in water. Experimental result, Key study

Difluoromethane 5 % (28 d) Detected in water. Experimental result, Key study

**12.3 Bioaccumulative potential
Product**

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in soil
Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

Component Information

Norflurane Henry's Law Constant: 8.580 MPa (25 °C)

**12.5 Results of PBT and vPvB
assessment
Product**

Not classified as PBT or vPvB.

12.6 Other adverse effects:

Global Warming Potential

Global warming potential: 1.387,2
 Contains fluorinated greenhouse gases When discharged in large quantities may contribute to the greenhouse effect. For GWP value of mixture and quantities, refer to container label.

Component Information

1,3,3,3-tetrafluoroprop-1-ene

EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs

- Global warming potential: 7 Annex 2: Other fluorinated greenhouse gases subject to reporting in accordance with Article 19; Section 1: Unsaturated



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 16/20

	hydro(chloro)fluorocarbons
2,3,3,3-Tetrafluoropropene	<p><u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs</u></p> <p>- Global warming potential: 4 Annex 2: Other fluorinated greenhouse gases subject to reporting in accordance with Article 19; Section 1: Unsaturated hydro(chloro)fluorocarbons</p>
Norflurane	<p><u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs</u></p> <p>- Global warming potential: 1430 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures</p>
Pentafluoroethane	<p><u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs</u></p> <p>- Global warming potential: 3500 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures</p>
Difluoromethane	<p><u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs</u></p> <p>- Global warming potential: 675 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures</p>

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:	Avoid discharges to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Refer to manufacturer or supplier for information on recovery or recycling.
Disposal methods:	Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.
<u>European Waste Codes</u>	
Container:	14 06 01*: chlorofluorocarbons, HCFC, HFC



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 17/20

SECTION 14: Transport information

ADR

14.1 UN Number: UN 3163
 14.2 UN Proper Shipping Name: LIQUEFIED GAS, N.O.S.(Difluoromethane, Pentafluoroethane)
 14.3 Transport Hazard Class(es)
 Class: 2
 Label(s): 2.2
 Hazard No. (ADR): 20
 Tunnel restriction code: (C/E)
 14.4 Packing Group: -
 14.5 Environmental hazards: Not applicable
 14.6 Special precautions for user: -

RID

14.1 UN Number: UN 3163
 14.2 UN Proper Shipping Name: LIQUEFIED GAS, N.O.S.(Difluoromethane, Pentafluoroethane)
 14.3 Transport Hazard Class(es)
 Class: 2
 Label(s): 2.2
 14.4 Packing Group: -
 14.5 Environmental hazards: Not applicable
 14.6 Special precautions for user: -

IMDG

14.1 UN Number: UN 3163
 14.2 UN Proper Shipping Name: LIQUEFIED GAS, N.O.S.(Difluoromethane, Pentafluoroethane)
 14.3 Transport Hazard Class(es)
 Class: 2.2
 Label(s): 2.2
 EmS No.: F-C, S-V
 14.4 Packing Group: -
 14.5 Environmental hazards: Not applicable
 14.6 Special precautions for user: -



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date:	09.11.2016	Version: 1.0	SDS No.: 000010035817
Last revised date:	13.05.2020		18/20

IATA

14.1 UN Number:	UN 3163
14.2 Proper Shipping Name:	Liquefied gas, n.o.s.(Difluoromethane, Pentafluoroethane)
14.3 Transport Hazard Class(es):	
Class:	2.2
Label(s):	2.2
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:Not applicable

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.
This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.



SAFETY DATA SHEET

C3H2F4 5,2962 %;C3H2F4 15,132 %;C2H2F4 17,7587 %;C2HF5 18,6912 %;CH2F2 43,1219 %

Issue Date: 09.11.2016 Version: 1.0 SDS No.: 000010035817
 Last revised date: 13.05.2020 19/20

SECTION 16: Other information

Revision Information: Not relevant.

Key literature references and sources for data: Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:
 Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
 European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
 European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
 European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.
 International Programme on Chemical Safety (<http://www.inchem.org/>)
 ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
 Matheson Gas Data Book, 7th Edition.
 National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
 The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
 The European Chemical Industry Council (CEFIC) ERICards.
 United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
 Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
 Substance specific information from suppliers.
 Details given in this document are believed to be correct at the time of publication.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 as amended.	Classification procedure
Gases under pressure, Liquefied gas	On basis of test data

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

Training information: Users of breathing apparatus must be trained. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Ensure operators understand the hazards.



SAFETY DATA SHEET

C₃H₂F₄ 5,2962 %;C₃H₂F₄ 15,132 %;C₂H₂F₄ 17,7587 %;C₂H₂F₅ 18,6912 %;CH₂F₂ 43,1219 %

Issue Date:	09.11.2016	Version: 1.0	SDS No.: 000010035817
Last revised date:	13.05.2020		20/20

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Liq. Gas, H280

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date:

13.05.2020

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.