



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
1/16

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Product name:** C2HF5 41,1838 %;C2H3F3 58,8162 %  
**Trade name:** R507, Freon™ 507  
**Other Name:** HFC-125 50 % (w/w); HFC-143a 50 % (w/w)

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses:** Industrial and professional. Perform risk assessment prior to use.  
Refrigerant.  
**Uses advised against** Consumer use.

**1.3 Details of the supplier of the safety data sheet**

**Supplier**  
Linde Gas AS  
Postboks 13 Nydalen  
N-0409 Oslo  
**Telephone:** +4723177200  
**E-mail:** sds.ren@linde.com

**1.4 Emergency telephone number: +47 22 59 13 00 (24h - Giftinformasjonssentralen)**

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 as amended.

**Physical Hazards**

Gases under pressure                      Liquefied gas                      H280: Contains gas under pressure; may explode if heated.

**2.2 Label Elements**



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
 Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
 2/16



**Signal Word:** Warning

**Hazard Statement(s):** H280: Contains gas under pressure; may explode if heated.

**Precautionary Statements**

**General** None.

**Prevention:** None.

**Response:** None.

**Storage:** P403: Store in a well-ventilated place.

**Disposal** None.

**Supplemental information**

EIGA-0783: Contains fluorinated greenhouse gases  
 EIGA-As: Asphyxiant in high concentrations.

**2.3 Other hazards** Contact with evaporating liquid may cause frostbite or freezing of skin.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Pentafluoroethane	C2HF5	41,1838%	354-33-6	01-2119485636-25	-	
1,1,1-Trifluoroethane	C2H3F3	58,8162%	420-46-2	01-2119492869-13	-	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

# # This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
 Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
 3/16

**Classification**

Chemical name	Classification		Notes
Pentafluoroethane	CLP:	Press. Gas Liquef. Gas;H280	
1,1,1-Trifluoroethane	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	

CLP: Regulation No. 1272/2008.

The full text for all H-statements is displayed in section 16.

**SECTION 4: First aid measures**

**General:** In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**4.1 Description of first aid measures**

**Inhalation:** In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**Eye contact:** Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

**Skin Contact:** Contact with evaporating liquid may cause frostbite or freezing of skin.

**Ingestion:** Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed:** Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Hazards:** Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

**Treatment:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
 Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
 4/16

**SECTION 5: Firefighting measures**

**General Fire Hazards:** Heat may cause the containers to explode.

**5.1 Extinguishing media**

**Suitable extinguishing media:** Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.

**Unsuitable extinguishing media:** None.

**5.2 Special hazards arising from the substance or mixture:** Fire or excessive heat may produce hazardous decomposition products.

**Hazardous Combustion Products:** If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Carbon oxides fluorocarbons Hydrogen fluoride ; Carbonyl difluoride

**5.3 Advice for firefighters**

**Special fire fighting procedures:** In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures:** Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date:	05.07.2018	Version: 1.0	SDS No.: 000010047426
Last revised date:	06.01.2021		5/16

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation.

6.4 Reference to other sections: Refer to sections 8 and 13.

**SECTION 7: Handling and storage:**

**7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

**7.2 Conditions for safe storage, including any incompatibilities:** Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

**7.3 Specific end use(s):** None.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
6/16

**SECTION 8: Exposure controls/personal protection**

**8.1 Control Parameters**

**Occupational Exposure Limits**

None of the components have assigned exposure limits.

**DNEL-Values**

Critical component	Type	Value	Remarks
Pentafluoroethane	Workers - Inhalation, Systemic, long-term	16444 mg/m3	Repeated dose toxicity
1,1,1-Trifluoroethane	Worker - inhalative, long-term - systemic	38800 mg/m3	-

**PNEC-Values**

Critical component	Type	Value	Remarks
Pentafluoroethane	Aquatic (freshwater)	0,1 mg/l	-
Pentafluoroethane	Sediment (freshwater)	0,6 mg/kg	-
1,1,1-Trifluoroethane	Aquatic (freshwater)	350 µg/l	-

**8.2 Exposure controls**

**Appropriate engineering controls:**

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.

**Individual protection measures, such as personal protective equipment**

**General information:**

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date:	05.07.2018	Version: 1.0	SDS No.: 000010047426
Last revised date:	06.01.2021		7/16

<b>Eye/face protection:</b>	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
<b>Skin protection</b>	
<b>Hand Protection:</b>	Guideline: EN 388 Protective gloves against mechanical risks. Additional Information: Wear working gloves while handling containers
<b>Body protection:</b>	No special precautions.
<b>Other:</b>	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
<b>Respiratory Protection:</b>	Not required.
<b>Thermal hazards:</b>	No precautionary measures are necessary.
<b>Hygiene measures:</b>	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
<b>Environmental exposure controls:</b>	For waste disposal, see section 13 of the SDS.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**Appearance**

Physical state:	Gas
Form:	Liquefied gas
Color:	C2HF5: Colorless C2H3F3: Colorless
<b>Odor:</b>	C2HF5: faint ethereal C2H3F3: Odorless
<b>Odor Threshold:</b>	Odor threshold is subjective and is inadequate to warn of over exposure.
<b>pH:</b>	Not applicable.
<b>Melting Point:</b>	No data available.
<b>Boiling Point:</b>	-46,7 °C
<b>Sublimation Point:</b>	Not applicable.
<b>Critical Temp. (°C):</b>	No data available.
<b>Flash Point:</b>	Not applicable to gases and gas mixtures.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
 Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
 8/16

Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Non-Flammable Gas
Flammability Limit - Upper (%):	Not applicable.
Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	1.282,6 kPa (25 °C)
Vapor density (air=1):	3,48 (calculated) (15 °C)
Relative density:	1,05 (25 °C)
Solubility(ies)	
Solubility in Water:	No data available.
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

**SECTION 10: Stability and reactivity**

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	None.
10.4 Conditions to avoid:	Open flames and high energy ignition sources. The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air or oxygen, the mixture may become flammable. Certain mixtures of HCFCs or HFCs with chlorine may become flammable or reactive under certain conditions.
10.5 Incompatible Materials:	No reaction with any common materials in dry or wet conditions. Alkali metals. Alkali earth metals. Chemically-active metals (such as calcium, powdered aluminum, zinc, and magnesium)





**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date:	05.07.2018	Version: 1.0	SDS No.: 000010047426
Last revised date:	06.01.2021		9/16

**10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information**

**General information:** None.

**11.1 Information on toxicological effects**

**Acute toxicity - Oral Product** Based on available data, the classification criteria are not met.

**Acute toxicity - Dermal Product** Based on available data, the classification criteria are not met.

**Acute toxicity - Inhalation Product** Based on available data, the classification criteria are not met.

**Component Information**  
1,1,1-Trifluoroethane NOAEL: 250000 ppm

**Repeated dose toxicity Component Information**  
Pentafluoroethane NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): >= 50.000 ppm(m) Inhalation Experimental result, Key study  
1,1,1-Trifluoroethane NOAEL (Rat(Female, Male), Inhalation): > 40.000 ppm(m) Inhalation Experimental result, Key study

**Skin Corrosion/Irritation Product** Based on available data, the classification criteria are not met.

**Serious Eye Damage/Eye Irritation Product** Based on available data, the classification criteria are not met.

**Respiratory or Skin Sensitization Product** Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity Product** Based on available data, the classification criteria are not met.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date:	05.07.2018	Version: 1.0	SDS No.: 000010047426
Last revised date:	06.01.2021		10/16

**Carcinogenicity**  
**Product** Based on available data, the classification criteria are not met.

**Reproductive toxicity**  
**Product** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure**  
**Product** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure**  
**Product** Based on available data, the classification criteria are not met.

**Aspiration Hazard**  
**Product** Not applicable to gases and gas mixtures..

**Other Relevant Toxicity Information**

Pentafluoroethane	Cardiac sensitisation threshold limit 100000 ppm Beagle (dog)NOAEC
	Cardiac sensitisation threshold limit 75000 ppm Beagle (dog)LOAEC

Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects. May produce irregular heart beat and nervous symptoms.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Acute toxicity**  
**Product** No ecological damage caused by this product.

**Acute toxicity - Fish**  
**Component Information**

Pentafluoroethane	LC 50 (Oncorhynchus mykiss, 96 h): 450 mg/l (semi-static) Remarks: Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study
1,1,1-Trifluoroethane	LC 10 (Oncorhynchus mykiss, 96 h): 40 mg/l (flow-through) Remarks: Experimental result, Key study



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
 Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
 11/16

**Acute toxicity - Aquatic Invertebrates**

**Component Information**

Pentafluoroethane	EC 50 (Daphnia magna, 48 h): > 200 mg/l (Static) Remarks: Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study
1,1,1-Trifluoroethane	EC 50 (Water flea (Daphnia magna)): 115 mg/l (calculated)

**Toxicity to microorganisms**

**Component Information**

1,1,1-Trifluoroethane	EC 50 (Alga, 72 h): 71 mg/l
-----------------------	-----------------------------

**Chronic Toxicity - Aquatic Invertebrates**

**Component Information**

Pentafluoroethane	EC 50 (16 d): 12 mg/l
-------------------	-----------------------

**Toxicity to Aquatic Plants**

**Component Information**

Pentafluoroethane	EC 50 (Green Algae, 72 h): 142 mg/l
-------------------	-------------------------------------

**12.2 Persistence and Degradability**

**Product**

Not applicable to gases and gas mixtures..

**Biodegradation**

**Component Information**

Pentafluoroethane	5 % (28 d) Detected in water. Experimental result, Key study
1,1,1-Trifluoroethane	2 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Supporting study

**12.3 Bioaccumulative potential**

**Product**

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in soil**

**Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date:	05.07.2018	Version: 1.0	SDS No.: 000010047426
Last revised date:	06.01.2021		12/16

**12.5 Results of PBT and vPvB assessment**

**Product** Not classified as PBT or vPvB.

**12.6 Other adverse effects:**

**Global Warming Potential**

Global warming potential: 3.984,9  
 Contains fluorinated greenhouse gases When discharged in large quantities may contribute to the greenhouse effect. For GWP value of mixture and quantities, refer to container label.

**Component Information**

Pentafluoroethane	<u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs</u> - Global warming potential: 3500 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures
1,1,1-Trifluoroethane	<u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs</u> - Global warming potential: 4470 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

<b>General information:</b>	Avoid discharges to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Refer to manufacturer or supplier for information on recovery or recycling.
<b>Disposal methods:</b>	Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <a href="http://www.eiga.org">http://www.eiga.org</a> ) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.
<b><u>European Waste Codes</u></b>	
<b>Container:</b>	14 06 01*: chlorofluorocarbons, HCFC, HFC



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018  
 Last revised date: 06.01.2021

Version: 1.0

SDS No.: 000010047426  
 13/16

**SECTION 14: Transport information**

**ADR**

14.1 UN Number: UN 1078  
 14.2 UN Proper Shipping Name: REFRIGERANT GAS, N.O.S.(Pentafluoroethane, 1,1,1-Trifluoroethane)  
 14.3 Transport Hazard Class(es)  
     Class: 2  
     Label(s): 2.2  
     Hazard No. (ADR): 20  
     Tunnel restriction code: (C/E)  
 14.4 Packing Group: -  
 14.5 Environmental hazards: Not applicable  
 14.6 Special precautions for user: -

**RID**

14.1 UN Number: UN 1078  
 14.2 UN Proper Shipping Name: REFRIGERANT GAS, N.O.S.(Pentafluoroethane, 1,1,1-Trifluoroethane)  
 14.3 Transport Hazard Class(es)  
     Class: 2  
     Label(s): 2.2  
 14.4 Packing Group: -  
 14.5 Environmental hazards: Not applicable  
 14.6 Special precautions for user: -

**IMDG**

14.1 UN Number: UN 1078  
 14.2 UN Proper Shipping Name: REFRIGERANT GAS, N.O.S.(Pentafluoroethane, 1,1,1-Trifluoroethane)  
 14.3 Transport Hazard Class(es)  
     Class: 2.2  
     Label(s): 2.2  
     EmS No.: F-C, S-V  
 14.4 Packing Group: -  
 14.5 Environmental hazards: Not applicable  
 14.6 Special precautions for user: -



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date:	05.07.2018	Version: 1.0	SDS No.: 000010047426
Last revised date:	06.01.2021		14/16

**IATA**

14.1 UN Number:	UN 1078
14.2 Proper Shipping Name:	Refrigerant gas, n.o.s.(Pentafluoroethane, 1,1,1-Trifluoroethane)
14.3 Transport Hazard Class(es):	
Class:	2.2
Label(s):	2.2
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code:** Not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**EU Regulations**

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:Not applicable

**National Regulations**

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.



**SAFETY DATA SHEET**

**C2HF5 41,1838 %;C2H3F3 58,8162 %**

Issue Date: 05.07.2018 Version: 1.0 SDS No.: 000010047426  
 Last revised date: 06.01.2021 15/16

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

Revision Information: Not relevant.

Key literature references and sources for data: Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:  
 Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).  
 European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.  
 European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>  
 European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.  
 International Programme on Chemical Safety (<http://www.inchem.org/>)  
 ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.  
 Matheson Gas Data Book, 7th Edition.  
 National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.  
 The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).  
 The European Chemical Industry Council (CEFIC) ERICards.  
 United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)  
 Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).  
 Substance specific information from suppliers.  
 Details given in this document are believed to be correct at the time of publication.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 as amended.	Classification procedure
Gases under pressure, Liquefied gas	On basis of test data

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.



**SAFETY DATA SHEET**

**C<sub>2</sub>H<sub>5</sub>F 41,1838 %;C<sub>2</sub>H<sub>3</sub>F<sub>3</sub> 58,8162 %**

Issue Date:	05.07.2018	Version: 1.0	SDS No.: 000010047426
Last revised date:	06.01.2021		16/16

**Training information:** Users of breathing apparatus must be trained. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Ensure operators understand the hazards.

**Classification according to Regulation (EC) No 1272/2008 as amended.**  
Press. Gas Liq. Gas, H280

**Other information:** Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**Last revised date:** 06.01.2021

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.